



## High Speed Steel SLOTING CUTTERS

Specifications Conform to :  
BS 122 : Part 1 : 1953  
Dimensions in Inches



Diameter + 0.045" 0.000	Bore + 0.00075" + 0.00025"	Width + 0.001" - 0.001"	Diameter + 0.045" 0.000	Bore + 0.00075" + 0.00025"	Width + 0.001" - 0.001"
2.1/2	1	1/4	4	1	1/2
2.1/2	1	5/16	4	1	5/8
2.1/2	1	3/8	4	1	3/4
2.1/2	1	7/16	4	1	7/8
2.1/2	1	1/2	4	1	1
3	1	1/4	5	1.1/4	1/4
3	1	5/16	5	1.1/4	5/16
3	1	3/8	5	1.1/4	3/8
3	1	7/16	5	1.1/4	7/16
3	1	1/2	5	1.1/4	1/2
3	1	5/8	5	1.1/4	5/8
3	1	3/4	5	1.1/4	3/4
3.1/2	1	1/4	5	1.1/4	7/8
3.1/2	1	5/16	5	1.1/4	1
3.1/2	1	3/8	6	1.1/4	1/4
3.1/2	1	7/16	6	1.1/4	5/16
3.1/2	1	1/2	6	1.1/4	3/8
3.1/2	1	5/8	6	1.1/4	7/16
3.1/2	1	3/4	6	1.1/4	1/2
3.1/2	1	7/8	6	1.1/4	5/8
4	1	1/4	6	1.1/4	3/4
4	1	5/16	6	1.1/4	7/8
4	1	3/8	6	1.1/4	1
4	1	7/16			

Cutters of Width 3/4" and above shall be supplied with left hand helical flutes.