

FINE GRIT RUBBER WHEELS



Rubber Control & Centreless Wheels

CUMI was the first abrasive manufacturer to produce Rubber Bonded Control wheels and Centreless wheels in India. The calendaring process enables excellent control in size & finish of components being ground.

The Rubber bonded Control and Centreless grinding wheels for

- Bearing Industry
- Hydraulic Industry
- General Purpose

- Automobile Industry
- Cutting Tool Industry

RUBBER CONTROL WHEEL

Product Features

- Longer wheel-life
- Superior form retention
- · Lesser dressing frequency
- Superior surface finish

Application				Product Recommendation		
For All Conventional Centreless Grinding				A80 R R		
For Fine & Precision Grinding				A120 R R		
For Fine & Precision Grinding				A150 R R		
Abrasive	Grit Size	Hardness	Bond Type	Dia (mm)	Thickness (mm)	
Brown Aloxide (A)	80 - 180	R - T	Rubber (R)	100 - 508	100 - 350	



Product Features

- Longer wheel-life
- Superior form retention
- Lesser dressing frequency
- Superior surface finish



Application	Grinding Type	Product Recommendation		
Taper Roller Outer Dia Grinding	Roughing	A80 LRT1, A80 LRT3, 65A80 LRT1		
Taper Roller Outer Dia Grinding	Finishing	A220 LRT1, 65A220 LRT1, A500 RBXR		
Taper Roller Outer Dia Grinding	Combined (Roughing & Finishing)	A80 LRT1		
Needle Roller Outer Dia Grinding	Roughing	A120 LRT1, A120 LRT3		
Needle Roller Outer Dia Grinding	Finishing	A220 LRT1		
Shock Absorber Outer Dia Grinding	Roughing	DA80 LRT1		
Shock Absorber Outer Dia Grinding	Semi Finishing	A220 LRT1		
Shock Absorber Outer Dia Grinding	Finishing	A500 RBXR, A320 RBXR		

Abrasive	Grit Size	Hardness	Bond Type	Dia (mm)	Thickness (mm)	ı
Brown Aloxide (A), 65A	80 - 220	L - M	Rubber (RT1, RT3, RT5, RT6)	300 - 610	80 - 250	